

EPACOL TK – TPU do produkcji klejów

EPACOL products have been developed to meet the requirements of the producers of solvent borne adhesives. They all show excellent resistance to hydrolysis and can be used in a wide range of solvents. We can supply even customized viscosity ranges, therefore do not hesitate to contact us!

EPACOL TK	Jedn.	TK 42	TK 42-300	TK 42-3000	TK 54	TK 54-3000	TK 560	TK 560-500	TK 560-3000	TK 570
lepkość w 15% roztworze MEK	mPaS	1700-2200	200-600	2800-3600	1700-2200	2200-3200	1700-2200	200-600	2500-3000	170-220
temperatura aktywacji	°C	55-60	55-60	55-60	60-65	60-65	65-70	65-70	65-70	70-75
krystaliczność		◆◆◆	◆◆◆	◆◆◆	◆◆◆	◆◆◆	◆◆◆◆	◆◆◆◆	◆◆◆◆	◆◆◆◆
odporność cieplna	°C	≥60	≥60	≥60	≥65	≥65	≥70	≥70	≥70	≥70

◆◆◆ duża
◆◆◆◆ b.duża

wszelkich informacji udzieli Państwu przedstawiciel i dystrybutor EPAFLEX POLYURETHANES w Polsce firma:

Milimex

ul. Poleczki 12

02-822 Warszawa

Tel. (22) 643 83 74-75; fax: (22) 643 83 76

www.milimex.waw.pl

milimex@milimex.com.pl